



### Materials and Resources (MR)

- ✓ Waste Management Planning
- ✓ Interiors Life Cycle Impact Reduction
- ✓ Environmental Product Declarations
- ✓ Sourcing of Raw Materials
- ✓ Material Ingredients
- ✓ Waste Management

### Indoor Environmental Quality (EQ)

- ✓ Low-Emitting Materials
  - ✓ Interior Lighting
  - ✓ Acoustic Performance
- Recycled Content:** up to 37%



Edge designation	Item number	Modular size (nominal)	lbs/sqft	sqft/carton	NRC	CAC	AC	Fire Class	Light Reflectance	Sag resistance (relative humidity)	Low VOC
	SQ 600	2' x 2' x 5/8"	0.38	112	0.75	20	-	A	0.85	up to 100 %	✓
	SQ 601	2' x 4' x 5/8"	0.38	112	0.75	20	-	A	0.85	up to 100 %	✓
	SQ 609	20" x 60" x 3/4"	0.45	83.33	0.75	20	-	A	0.85	up to 100 %	✓
	SQ 610	2' x 5' x 3/4"	0.45	100	0.75	20	-	A	0.85	up to 100 %	✓
	SLN 620	2' x 2' x 5/8"	0.47	56	0.75	20	-	A	0.85	up to 100 %	✓
	SLN 621	2' x 4' x 5/8"	0.47	112	0.75	20	-	A	0.85	up to 100 %	✓
	SL 660	2' x 2' x 5/8"	0.47	56	0.75	20	-	A	0.85	up to 100 %	✓
	SL 661	2' x 4' x 5/8"	0.47	112	0.75	20	-	A	0.85	up to 100 %	✓

15/16" Suspension Systems	9/16" Suspension Systems
1200, 200 and Fire rated systems	4000, 4500, 4600 and Fire rated systems
<p>SQ      SL</p>	<p>SQ      SLN - Tempra      SLN - Ultralite 1/4"      SLN - Ultralite 1/8"</p>



Budget: \$\$\$\$\$

**Material**

Stone wool (Mineral Wool) ceiling tiles with factory painted glass scrim surface  
ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



**Fire Performance**

Surface burning characteristics:  
UL723 (ASTM E84) Flame Spread Index: 0  
Smoke Developed Index (UL Labeled): 5  
CAN/ULC S102 Flame Spread Index: 5  
Smoke Developed Index: 0



**Environment**

Fully recyclable



**Thermal Insulation**

R Value (BTU Units): 2.2 - 2.6  
RSI Value (Watts Units): 0.39 - 0.46



**VOC Emissions**

All Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



**Warranty Information**

30-Year Limited Product Warranty.  
See [www.rockfon.com](http://www.rockfon.com)



**Hygiene**

Stone wool provides no sustenance to microorganisms



**Cleaning**

- Vacuum

Rockfon® is a registered trademark  
of the ROCKWOOL Group.

10.2018 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

4849 S. Austin Ave., Chicago, IL 60638 USA  
Tel. +1-800-323-7164  
Fax. +1-800-222-3744  
[www.rockfon.com](http://www.rockfon.com)  
[cs@rockfon.com](mailto:cs@rockfon.com)  
SNL150024

