



# Rockfon® Contour™

## LEED® v4 Highlights






### Materials and Resources (MR)

- ✓ Waste Management Planning
- ✓ Interiors Life Cycle Impact Reduction
- ✓ Environmental Product Declarations
- ✓ Sourcing of Raw Materials
- ✓ Material Ingredients
- ✓ Waste Management

### Indoor Environmental Quality (EQ)

- ✓ Low-Emitting Materials
- ✓ Interior Lighting
- ✓ Acoustic Performance

**Recycled Content:** up to 42%

Edge designation		Item number	Modular size (nominal)	lbs/unit	units/carton	 Fire Class	 Light Reflectance	 Sag resistance* (relative humidity)	 Low VOC
SQc 	SQc	7200	12" x 48" x 2"	5.07	12	A	0.79	up to 100 %	✓
	SQc	7225	24" x 48" x 2"	10.14	6	A	0.79	up to 100 %	✓

\*Rockfon Contour is not suitable for use in swimming pools or outdoors.



Budget: \$\$\$\$

**Material**

Stone wool (Mineral Wool) frameless baffle with factory painted glass scrim on both sides  
 ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



**Fire Performance**

Surface burning characteristics:  
 UL723 (ASTM E84) Flame Spread Index: 0  
 Smoke Developed Index (UL Labeled): 5  
 CAN/ULC S102 Flame Spread Index: 5  
 Smoke Developed Index: 0



**Environment**

Fully recyclable



**VOC Emissions**

All Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



**Warranty Information**

30-Year Limited Product Warranty.  
 See [www.rockfon.com](http://www.rockfon.com)



**Hygiene**

Stone wool provides no sustenance to microorganisms



**Cleaning**

- Vacuum



**Acoustical Properties**

		Sabins per baffle					
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
Tested in ISO Type J mounting: 3 x 15'9" rows, 2'9" row spacing	24" x 48" x 2"	3.5	4.0	7.1	8.5	8.4	7.8

Rockfon® is a registered trademark  
of the ROCKWOOL Group.

10.2018 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

4849 S. Austin Ave., Chicago, IL 60638 USA  
Tel. +1-800-323-7164  
Fax. +1-800-222-3744  
[www.rockfon.com](http://www.rockfon.com)  
[cs@rockfon.com](mailto:cs@rockfon.com)  
SNL150024

