

Materials and Resources (MR)

- ✓ Waste Management Planning
- ✓ Interiors Life Cycle Impact Reduction
- ✓ Environmental Product Declarations
- ✓ Sourcing of Raw Materials
- ✓ Material Ingredients
- ✓ Waste Management

Indoor Environmental Quality (EQ)


- ✓ Low-Emitting Materials
 - ✓ Interior Lighting
 - ✓ Acoustic Performance
- Recycled Content:** up to 34%



Edge designation	Item number	Modular size (nominal)	lbs/sqft	sqft/carton	NRC	CAC	AC	Fire Class	Light Reflectance	Sag resistance (relative humidity)	Low VOC
	SQ 4100	2' x 2' x 3/4"	0.45	80	0.85	22	-	A	0.86	up to 100 %	✓
	SQ 4200	2' x 2' x 1 1/2"	0.82	40	0.85	22	-	A	0.86	up to 100 %	✓

15/16" Suspension Systems

1200, 200 and Fire rated systems





Budget: \$\$\$\$

Material

Stone wool (Mineral Wool) ceiling tiles with factory painted reinforced glass scrim to increase impact resistance
 ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern E



Fire Performance

Surface burning characteristics:
 UL723 (ASTM E84) Flame Spread Index: 0
 Smoke Developed Index (UL Labeled): 5
 CAN/ULC S102 Flame Spread Index: 5
 Smoke Developed Index: 0



Environment

Fully recyclable



Thermal Insulation

R Value (BTU Units): 2.6 - 5.3
 RSI Value (Watts Units): 0.46 - 0.92



VOC Emissions

All Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



Warranty Information

30-Year Limited Product Warranty.
 See www.rockfon.com



Hygiene

Stone wool provides no sustenance to microorganisms



Cleaning

- Vacuum
- Damp cloth



Impact Resistance

Rockfon Impact's capability to withstand incidental or occasional ball impact has been tested. For more details, please contact customer service.

Rockfon® is a registered trademark
of the ROCKWOOL Group.

10.2018 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

4849 S. Austin Ave., Chicago, IL 60638 USA
Tel. +1-800-323-7164
Fax. +1-800-222-3744
www.rockfon.com
cs@rockfon.com
SNL150024

